

IMPROVED PERSONALISED DATA MODELLING USING PARAMETER  
INDEPENDENT FUZZY WEIGHTED K-NEAREST NEIGHBOUR FOR  
SPATIO/SPECTRO-TEMPORAL DATA

MOHD HAFIZUL AFIFI BIN ABDULLAH


A thesis submitted in  
fulfilment of the requirement for the award of the  
Master of Information Technology



Faculty of Computer Science and Information Technology  
Universiti Tun Hussein Onn Malaysia

JANUARY 2021

I hereby declare that the work in this project report is my own except for quotations and summaries which I have duly acknowledged.

Student : ..... 

MOHD HAFIZUL AFIFI BIN ABDULLAH

Date : ..... 3 / 1 / 2021

Supervisor : ..... 

DR. MUHAINI BINTI OTHMAN

Date : ..... 3 / 1 / 2021

Co-Supervisor : ..... 

ASSOC. PROF. DR. SHAHREEN BINTI KASIM

Date : ..... 3 / 1 / 2021



PTTA UTHM  
PERPUSTAKAAN TUN AMINAH

*To my beloved Mama and Abah.*

*To my brothers and sisters.*

*Les préférences, Noureen Talpur.*

*Thanks for being there and appreciating those little things.*

Though Absent You Are Always Near  
Still Loved, Still Missed, Still Very Dear  
You Are an Inspiration to All–Tok Ayah



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## ACKNOWLEDGEMENT

In the name of Allah, the Most Gracious, the Most Merciful. I praise and thank Allah for His blessings uncounted in my life and His willing; I was able to complete this research successfully. This dissertation would not have been possible without the guidance, help, and support of many people contributed and extended their valuable assistance in the preparation and completion of this research. I take this opportunity to express my profound sense of gratitude and respect to all those people.

First and foremost, I would like to express my sincere appreciation to my main supervisor Dr. Muhaini binti Othman and my co-supervisor Prof. Madya Dr. Shahreen binti Kasim for their guidance and endless support from the initial to the final level, for their patience, motivation, enthusiasm, and immense knowledge. Their feedback, editorial comments, and suggestions were also invaluable for writing this thesis. I appreciate it.

In preparing this research, my gratitude is extended to Universiti Tun Hussein Onn Malaysia (UTHM) for supporting this research under the Fundamental Research Grant Scheme. I would like to gratefully thank the Centre for Graduate Studies (CGS) and the Research, Innovation, Commercialization, and Consultancy Office (ORICC) for their hospitality during my study. I also wish to say thank to the Faculty of Computer Science and Information Technology Postgraduate friends and staff who had supported my research work in one way or another.

A special thanks to my beloved family, for their continuous prayer, encouragement, love, support, patience, and care whenever I needed during these challenging days. I dedicate this work to all of you. My overwhelming gratitude to all my friends who have been together with me, thanks for love, care, concern, and support. Lastly, it is a pleasure to thank all those who have helped either directly or indirectly. Thank you.

## ABSTRACT

Machine learning technologies have been growing rapidly in recent years. Researchers have come up with several data processing architectures, enabling machines to consume, interpret, and produce understandable output from real-world data to improve the quality of our lives. The NeuCube architecture is a data processing architecture for spatio/spectro-temporal data which consists of four main modules: a spike encoding module, a recurrent SNN reservoir, an output module, and an optimization module. Despite it has been utilised on many various applications, most improvement of the architecture focuses on user experience rather than improving the result accuracy. Upon exploration of the architecture, the weighted  $k$ -nearest neighbours algorithm used for the classification module is found to be prone to misclassification as it relies solely on the majority voting rule to determine the class for new data vector. Additionally, it does not consider the class-specific fuzzy weight information during the classification process. Therefore, a data modelling mechanism which implements PifwkNN classifier algorithm for improving the overall classification accuracy of the NeuCube architecture has been proposed. The proposed data modelling applies an additional class-specific fuzzy weight information to new data vectors during the classification process. In this research, the optimal parameters set for experiments has also been identified. The approach has been validated by using the Kuala Krai Rainfall Dataset, Dow Jones Index Data Set, and Gold Price and Performance Dataset for the 3-days earlier and 1-day earlier event prediction. From the experiments, the improved personalised data modelling using PifwkNN classifier has shown a significant increase in terms of overall classification accuracy as compared to the conventional MLP,  $fkNN$ , and NeuCube with  $wkNN$  classifier.

## ABSTRAK

Saban tahun, teknologi pembelajaran mesin telah berkembang dengan pantas. Para penyelidik telah menghasilkan beberapa seni bina pemprosesan data yang membolehkan mesin menerima, mentafsir, dan menjana output dari data dunia nyata bagi tujuan memperbaiki taraf hidup kita. NeuCube merupakan sebuah seni bina pemprosesan data bagi data berbentuk spatio/spectro-temporal yang mengandungi empat modul utama yakni: modul pengkodan lonjakan, takungan SNN berulang, modul output, dan modul pengoptimum. Walaupun telah digunakan secara meluas, sebahagian besar fokus penambahbaikan seni bina ini menjurus pada pengalaman pengguna berbanding bagi meningkatkan ketepatan hasil. Melalui penerokaan, telah didapati bahawa algoritma *weighted k-nearest neighbours* yang digunakan dalam modul klasifikasi terdedah kepada ralat pengelasan atas sebab proses pengelasan tersebut bergantung sepenuhnya terhadap *majority voting rule* bagi menentukan kelas bagi vektor data baru. Tambahan, algoritma tersebut tidak mengambil kira pemberat fuzzy kelas khusus semasa proses klasifikasi. Justeru, sebuah mekanisma pemodelan data menggunakan pengkelas PifwkNN telah dicadangkan bagi menggantikan pengelas sedia ada bagi menambah baik ketepatan proses pengelasan data. Kaedah yang dicadangkan ini menggunakan maklumat pemberat fuzzy kelas khusus terhadap data baharu semasa proses pengelasan dilaksanakan. Dalam penyelidikan ini, parameter optimal bagi menjalankan eksperimen juga telah dikenalpasti. Kaedah ini telah disahkan menggunakan Dataset Taburan Hujan Kuala Krai, Dataset Indeks Dow Jones, dan Dataset Prestasi Harga Emas bagi jangkaan seawal 3-hari sebelum dan 1-hari sebelum berlakunya sesuatu kejadian. Melalui eksperimen tersebut, kaedah menggunakan NeuCube beserta pengelas PifwkNN telah memaparkan peningkatan yang signifikan dari sudut ketepatan pengelasan secara keseluruhan jika dibandingkan dengan kaedah konvensional MLP, *fkNN*, dan NeuCube beserta pengelas *wkNN*.

## TABLE OF CONTENT

<b>DECLARATION</b>	<b>iii</b>
<b>DEDICATION</b>	<b>iv</b>
<b>ACKNOWLEDGEMENT</b>	<b>v</b>
<b>ABSTRACT</b>	<b>vi</b>
<b>ABSTRAK</b>	<b>vii</b>
<b>TABLE OF CONTENTS</b>	<b>viii</b>
<b>LIST OF TABLES</b>	<b>xi</b>
<b>LIST OF FIGURES</b>	<b>xiii</b>
<b>LIST OF SYMBOLS AND ABBREVIATIONS</b>	<b>xvi</b>
<b>LIST OF PUBLICATIONS</b>	<b>xvii</b>
<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1 Research background	1
1.2 Problem statement	3
1.3 Objectives	5
1.4 Scope of the research	5
1.5 Significance of research	6
1.6 Thesis organisation	7
<b>CHAPTER 2 LITERATURE REVIEW</b>	<b>8</b>
2.1 Introduction	8
2.2 History of neural networks	8
2.3 Evolution of neural networks	10

2.4	Environmental events and the risk of flood	15
2.4.1	Predictability of flood occurrences based on variables patterns	17
2.4.2	Spatio/Spectro-Temporal Data	23
2.4.3	Understanding data patterns in nature	24
2.5	Inductive and transductive reasoning	25
2.6	Global, local, and personalised modelling	28
2.6.1	Global modelling	28
2.6.2	Local modelling	30
2.6.3	Personalised modelling	31
2.6.4	Comparative analysis of different data modelling techniques	32
2.7	Classification algorithms for personalised modelling	33
2.7.1	$k$ -nearest neighbour ( $k$ NN)	33
2.7.2	Fuzzy $k$ -nearest neighbour ( $fk$ NN)	34
2.7.3	Weighted $k$ -nearest neighbour ( $wk$ NN)	35
2.7.4	Parameter independent fuzzy-weighted $k$ -nearest neighbour (PIfwkNN)	36
2.7.5	Comparative analysis of different classification algorithms	38
2.8	Related works	39
2.9	Research gap	42
2.10	Chapter summary	43
<b>CHAPTER 3</b>	<b>RESEARCH METHODOLOGY</b>	<b>44</b>
3.1	Introduction	44
3.2	Research phases	45
3.3	Research framework	47
3.4	Dataset collection for experiments	53
3.4.1	Dataset 1: Kuala Krai Rainfall Dataset	54
3.4.2	Dataset 2: Dow Jones Index Data Set	56



PTTA  
PERPUSTAKAAN TUNJUKKAN AMINAH



3.4.3	Dataset 3: Gold Price and Performance	58
	Dataset	
3.5	Data preprocessing and partitioning	60
3.6	The proposed approach	62
3.6.1	Encode input neurons	64
3.6.2	Unsupervised training in SNN reservoir	66
3.6.3	Supervised training in eSNN classifier	67
3.6.4	Calculate accuracy	70
3.6.5	Save the optimised model	71
3.6.6	Cross-validation	72
3.6.7	Parameter optimisation module	73
3.7	Chapter summary	74
<b>CHAPTER 4</b>	<b>RESULTS AND ANALYSIS</b>	<b>75</b>
4.1	Introduction	75
4.2	Experiment profiles	75
4.2.1	Experiment 1: Kuala Krai Flood Risk	76
4.2.2	Experiment 2: Dow Jones Index	79
4.2.3	Experiment 3: Gold Price and Performance	81
4.3	Analysis and discussion	83
4.4	Chapter summary	85
<b>CHAPTER 5</b>	<b>CONCLUSION</b>	<b>86</b>
5.1	Overview	86
5.2	Research contributions	87
5.3	Recommendations for future research	88
	<b>REFERENCES</b>	<b>89</b>
	<b>VITA</b>	<b>97</b>



## LIST OF TABLES

2.1	Few studies that have the impact of neural network development	10
2.2	Comparison between global, local, and personalised modelling techniques	32
2.3	$k$ NN, $wk$ NN, PIfw $k$ NN classification algorithm	38
3.1	Layers within $wk$ NN and PIfw $k$ NN classifier	52
3.2	Metadata of Kuala Krai Rainfall Dataset	54
3.3	Excerpt for the Kuala Krai Rainfall Dataset	55
3.4	Metadata of Dow Jones Index Data Set	56
3.5	Excerpt for the Dow Jones Index Data Set	57
3.6	Metadata of Gold Price and Performance Dataset	58
3.7	Excerpt for the Gold Price and Performance Dataset	59
3.8	Dataset distribution for training and testing	60
3.9	Settings used for network initialisation	65
3.10	Standard training $wk$ NN model and the proposed training PIfw $k$ NN model	70
3.11	Pseudocode for calculation of accuracy in NeuCube	71
3.12	Settings used for the parameter optimisation module	74
4.1	Optimal parameters for MLP classifier for Kuala Krai Rainfall Dataset	76
4.2	Optimal parameters for the experiment using $wk$ NN classifier and PIfw $k$ NN classifiers for Kuala Krai Rainfall Dataset	77

4.3	Comparison between MLP, <i>fkNN</i> , <i>wkNN</i> , and the proposed <i>PIfwkNN</i> classifier for Kuala Krai Rainfall Dataset	77
4.4	Optimal parameters for MLP classifier for Dow Jones Index Data Set	79
4.5	Optimal parameters for the experiment using <i>wkNN</i> classifier and <i>PIfwkNN</i> classifiers for Dow Jones Index Data Set	79
4.6	Comparison between MLP, <i>fkNN</i> , <i>wkNN</i> , and the proposed <i>PIfwkNN</i> classifier for Dow Jones Index Data Set	80
4.7	Optimal parameters for MLP classifier for Gold Price and Performance Dataset	81
4.8	Optimal parameters for the experiment using <i>wkNN</i> classifier and <i>PIfwkNN</i> classifiers for Gold Price and Performance Dataset	82
4.9	Comparison between MLP, <i>fkNN</i> , <i>wkNN</i> , and the proposed <i>PIfwkNN</i> classifier for Gold Price and Performance Data Set	82
4.10	Comparison between results obtained using MLP, <i>fkNN</i> , and <i>wkNN</i> versus the proposed <i>PIfwkNN</i> classifier on three real-world datasets	84



PTT AUTHIM  
PERPUSTAKAAN TUNKU TUN AMINAH

## LIST OF FIGURES

2.1	Talairach applet [24]–[26]	9
2.2	The McCulloch-Pitts neuron model	11
2.3	Feedforward neural network	13
2.4	Leaky integrate-and-fire model of spiking neuron [11]	14
2.5	Projection of proportion of Malaysian urban and rural areas [4]	16
2.6	Graph of water level measurement of Sungai Kelantan at the Kuala Krai cross-section against lag days (with risk factor)	18
2.7	Graph of air humidity level measured at the Kuala Krai meteorology station against lag days (with risk factor)	18
2.8	Graph of temperature measurement at the Kuala Krai meteorology station against lag days (with risk factor)	19
2.9	Graph of monthly rainfall measurement at the Kuala Krai meteorology station against lag days (with risk factor)	20
2.10	Graph of daily rainfall measurement at the Kuala Krai meteorology station against lag days (with risk factor)	20

2.11	Graph of wind speed measurement at the Kuala Krai meteorology station against lag days (with risk factor)	21
2.12	Designated critical levels at a flood warning station [43]	22
2.13	River cross-section and designated critical water level at Kuala Krai flood warning station	22
2.14	The SSTD are designed as stacks of matrices which can be fed into NeuCube architecture for data encoding process	23
2.15	Model $M_i$ is produced using inductive inference method [11]	26
2.16	Model $M_i$ is produced using transductive inferencing [11]	27
2.17	Categorization of data modelling techniques and algorithms based on reasoning approaches	28
2.18	Simple linear SVM separates data vectors into two different classes by a maximum margin hyperplane [11]	30
2.19	$k$ NN learning algorithm majority voting rule to determine the class label of the new data vector with parameter $k=3$ [10]	34
2.20	Comparison between the (a) classification without feature weighting and (b) classification with class-specific feature weighting	37
2.21	Schematic diagram of PMeSNNr architecture [6]	39
2.22	NeuCube functional diagram [62]	40
3.1	Flowchart of the research phases	45
3.2	Research framework	47
3.3	Data design procedure requires CSV data to be formatted to MATLAB data file	48



PTTA UTHM  
PERPUSTAKAAN TUNJUKKAN AMINAH

3.4	The sequence of data are fed in a backward arrangement	48
3.5	The eSTDM principle	49
3.6	The classifier module working mechanism	50
3.7	Visualisation of modification of classifier module	51
3.8	The experimental setup	53
3.9	Visualisation of distribution for training and testing for all selected datasets	61
3.10	(a) Schematic diagram of eSTDM principle [36], [49], (b) Flowchart of the eSTDM principle	62
3.11	NeuCube model training	63
3.12	NeuCube random connection before network initialisation	65
3.13	Visualisation of connectivity and spiking activity within SNNr [4]	66
3.14	Rank Order Coding [70]	67
3.15	eSNN for classification using ROC	68
3.16	Cross-validation configuration panel	72
3.17	Result of the LOOCV	73



PTT AUTHIM  
PERPUSTAKAAN TUNKU TUN AMINAH

## LIST OF SYMBOLS AND ABBREVIATIONS

AER	-	Address-Event-Representation
eSNN	-	evolving Spiking Neural Network
eSTDM	-	evolving Spatio-Temporal Data Modelling
$k$ NN	-	$k$ -Nearest Neighbours
$f$ $k$ NN	-	Fuzzy $k$ -Nearest Neighbour
$w$ $k$ NN	-	Weighted $k$ -Nearest Neighbour
PIfwkNN	-	Parameter Independent Fuzzy Weighted $k$ -NN
HPC-EC	-	Hippocampal-entorhinal cortex
LOOCV	-	Leave-One-Out Cross-Validation
MLP	-	Multilayer Perceptron
PMeSNNr	-	Personalised Modelling evolving Spiking Neural Network Reservoir
PSP	-	Postsynaptic Potential
RNN	-	Recurrent neural network
SNN	-	Spiking Neural Network
SNNr	-	Spiking Neural Network Reservoir
SSTD	-	Spatio/Spectro-Temporal Data
STDP	-	Spiking Time Dependent Plasticity
SVM	-	Support Vector Machine
UCIMLR	-	University of California Irvine Machine Learning Repository

## LIST OF PUBLICATIONS

### Journal/Conference:

- (i) Abdullah, M. H. A., Othman, M., Kasim, S., Saharuddin, S. S., & Mohamed, S. A. (2020). A Spiking Neural Networks Model with Fuzzy-Weighted  $k$ -Nearest Neighbour Classifier for Real-World Flood Risk Assessment. In *International Conference on Soft Computing and Data Mining* (pp. 222-230). Springer, Cham.
- (ii) Abdullah, M. H., Othman, M., Kasim, S., & Mohamed, S. A. (2019). Evolving spiking neural networks methods for classification problem: a case study in flood events risk assessment. *Indonesian Journal of Electrical Engineering and Computer Science*, 16(1), 222-229.
- (iii) Mohamed, S. A., Othman, M., & Abdullah, M. H. (2019). A review on data clustering using spiking neural network (SNN) models. *Indonesian Journal of Electrical Engineering and Computer Science*, 15(3), 1392-1400.
- (iv) Othman, M., Mohamed, S. A., Abdullah, M. H., Yusof, M. M., & Mohamed, R. (2018). A Framework to Cluster Temporal Data Using Personalised Modelling Approach. *Advances in Intelligent Systems and Computing*, 181-190.

### Book Chapter:

- (i) Abdullah, M. H., Othman, M., & Kasim, S. (2017). Comparative Analysis Of Spatio/Spectro-Temporal Data Modelling Techniques. In *Data Engineering And Information Security Series 1* (1st ed.). Batu Pahat, Malaysia: Penerbit UTHM.



## CHAPTER 1

### INTRODUCTION

#### 1.1 Research background

Early event prediction is made possible by analysing patterns in event occurrences given that sufficient knowledge of previous similar occurrences is provided. Such analysis is required in assisting government and non-government organisations in formulating an early prediction system, which is capable of providing an early alert towards the risk of a natural disaster such as the risk of flood occurrence, which happens every year in certain areas of Malaysia. To come up with such a sophisticated system, a detection mechanism needs to be addressed, where it consumes real-world data for training, validating, and optimization of a prediction model over time.

Most of the time, real-world data such as environmental data and ecological data is needed to be presented in the form of spatio/spectro-temporal data (SSTD) as it captures measurements of all variables within the environment on time (include temporal component). For instance, all environmental-related variables, which contribute to the risk of flooding is captured every few hours and are represented in the form of SSTD. Therefore, by having these variables measured over time, the prediction system can capture the interrelationship between the variables over time. Next, the optimised and validated prediction model is useful for application in the real world for predicting the probability and the risk of events occurrences, such as flood prediction. In this research, a case study of flood risk assessment is adapted for creating an improved personalised data

modelling by analysing the environmental data collected in the form of SSTD to create an earlier risk assessment for flood risk occurrence.

Two reasoning theories that can be applied for creating data models are inductive reasoning and transductive reasoning. Inductive reasoning creates a generalised model from the entire set of historical data while transductive reasoning creates a model based on historical data and adapts new data to improve the existing model. In most cases, inductive reasoning is sufficient; however, transductive reasoning is more suitable for individual or personalised cases, such as situations related to clinical and medical conditions, geological problems, or weather and disaster prediction. Most of the data related to the environment are in the form of complex SSTD, which requires pre-processing so that it is compatible to be fed to the network.

Global modelling, local modelling, and personalised modelling are introduced based on the previously discussed reasoning theories [1]. Global modelling is created from the entire problem space, hence offers a general interpretation of the data [1], [2]. Global models are however not suitable for problems with a dynamic environment as the model does not evolve based on the new data [1], [2]. Local modelling aims to solve the adaptive issue of global models (mostly are based on clustering techniques), hence providing more adaptable behaviour to new data vectors [1]. Personalised modelling, on the other hand, creates a model for only a single data vector in a local domain [2].

Through a series of studies, Kasabov *et al.* [3]–[6] has introduced the NeuCube architecture for mapping and learning neuronal spikes from SSTD. The architecture has been implemented on various applications such as for understanding brain data [4], [7], [8], solving ecological problems [6], [9], stroke risk prediction [3], [10], [11], video and audio pattern recognition [12], [13], and flood risk assessment [14], [15]. The studies and implementation have provided promising results produced by the architecture. Despite being able to produce a result with high accuracy, the mechanism of classification in the NeuCube architecture is prone to misclassification as it utilises the weighted  $k$ -nearest neighbour ( $wkNN$ ), which relies solely on the majority voting rule to determine the class during the classification process [3], [4], [10]. The  $wkNN$  classifier does not consider the membership of each new data vector in contribution towards the actual class.

Therefore, this work attempts to provide improved personalised data modelling by employing a parameter independent fuzzy weighted  $k$ -nearest neighbour (PIfwkNN) for SSTD. The PIfwkNN classifier utilises class-specific weights information during the classification process, therefore providing a clear advantage towards the mechanism of constructing the personalised data model. Several techniques incorporating spiking neural networks (SNN) methods are explored, compared, and contrasted, whereby a suitable approach is validated with real-world flood event data and other benchmark datasets.

## 1.2 Problem statement

Among many soft-computing and machine learning algorithms existing today, spiking neural network has gained popularity due to its capability to encode hidden patterns between variables and time [2]. A novel NeuCube architecture [3] consisting of an evolving spiking neural network (eSNN) mechanism for personalised modelling method has been introduced to process and analyze SSTD. The architecture has been implemented in various applications including for understanding brain data [4], [7], [8], solving ecological problems [6], [9], stroke risk prediction [3], [10], [11], video and audio pattern recognition [12], [13], as well as flood risk assessment [14], [15]. In a study conducted by Capecci *et al.* [7], the NeuCube architecture has been used for the prediction of response towards treatments and drug dosage effects using trained EEG data on the created model. Most of the NeuCube implementation papers have presented that the architecture is capable of producing a higher accuracy result as compared to using traditional statistical and artificial intelligence methods. However, upon the exploration of the framework, shortcomings have been found in the classifier module.

Previously, based on the existing NeuCube architecture, the output was classified solely based on majority voting rule according to the weighted  $k$ -nearest neighbours for a classification task [3], [4], [10]. Albeit the one-pass learning offered in NeuCube is relatively fast and suitable for SSTD processing [11], the neurons may be inaccurately labelled due to a lack of references to the similar neighbouring neurons. The  $wkNN$  classifier used in the existing NeuCube architecture does not consider the membership of each variable in contribution to the correct class. There is a risk of incorrect classification

due to neglecting the known class-specific weight during the classification process. On the other hand, the proposed PIfwkNN classifier can solve this issue as it considers class-specific weight during the classification process. By considering the known class-specific weights during classification, improved overall classification accuracy can be produced since the network utilized an additional reliable knowledge to create a more reliable information-based network.

The second drawback of the existing wkNN classifier is that it cannot assign fuzzy membership value to each of the new and existing data vectors; therefore, the selection of class for the new data vector is made in Boolean (0 or 1). This means each data vector can only belong to one class, regardless of its actual membership to another class. Due to this situation, the result generated by the current classifier is misrepresented, as the degree of membership of each data vector is not taken into account during the classification process. By implementing the PIfwkNN algorithm, the classifier can apply fuzzy membership allowing each data vector to have membership degree to multiple classes, therefore, allowing the data vector to be assigned to a class where it is related.

Third, to create an optimal network, there is a challenge to fine-tune all parameters during the training and validation of the personalised data model. It is necessary to fine-tune all parameters for the experimentation to produce the highest accuracy result at the earliest time possible without overfitting the network. Therefore, finding all optimised parameters for creating a personalised model is a challenge this research will tackle.

There is no doubt that NeuCube architecture is useful for predicting and classifying data across different domains. Applying an algorithm such as PIfwkNN produces a more reliable knowledge by associating class-specific weights (which act as membership functions) for a better classification rather than solely depend on the majority voting for assigning classes. The proposed PIfwkNN algorithm combines both the capability of fuzzy membership with the majority voting rule for assigning classes more accurately. This research introduces an interest to create improved personalised data modelling using PIfwkNN for SSTD to improve overall classification accuracy.

To summarise, the statement of problems is *“The current wkNN classifier in the NeuCube architecture executes classification solely based on the majority voting rule based on the selected nearest neighbours, without considering the membership of each*

*new data vector in contribution towards to the actual class. Therefore, given the complex dimension of the SSTD, the challenge is to propose and justify a suitable classifier, which can produce a higher overall accuracy as compared to the existing wkNN classifier used in the NeuCube architecture without losing the valuable information. It can be executed within the spatial and temporal component of the data by considering the interrelationship between both components during the process.”*

### **1.3 Objectives**

This research embarks the following objectives:

- i. To propose a data modelling, which implements PIfwkNN classifier algorithm for improving the overall classification accuracy of the NeuCube architecture.
- ii. To find optimal parameters for the improved personalized data modelling utilizing PIfwkNN classifier.
- iii. To evaluate and compare the performance of the personalised data modelling with PIfwkNN classifier against the existing wkNN classifier, MLP, and fkNN classifier in terms of classification accuracy.

### **1.4 Scope of research**

This study is limited to an investigation of a suitable classifier for the existing NeuCube framework, allowing the architecture to produce a better accuracy classification result as compared to the existing classifier. The dataset used is taken from a real-world case study data which covers Kuala Krai historical environmental data from 2012-2016 (5 years) provided by the Malaysian Meteorological Department.

### 1.5 Significance of research

This research contributes to the body of knowledge in terms of providing a much suitable algorithm to be used in the NeuCube architecture, which utilizes eSNN engine. This research presents an improvement of overall classification result accuracy by implementing the proposed PIfw $k$ NN classifier. The proposed PIfw $k$ NN classifier is capable of producing a higher classification accuracy result by allowing each data vector to have a specific-class fuzzy weight. Therefore, the determination of the class for new data vectors considers the fuzzy membership value as well; instead of only being determined by the majority voting rule based on the  $k$ -nearest neighbour.

In the real world, the ability to produce personalised data models can be applied to environmental cases and benefit society with the development of an event management system. The research outcome can be implemented in the disaster alert system, where the engine of the alert system is capable of predicting the risk of environmental disasters such as floods, tsunamis, earthquakes, and many others. The development of such technology could help to reduce the risk of accidental death and property losses by providing an earlier alert to be broadcast to a high-risk area. Another possible application of this research is to integrate it into the Disaster Management Decision Support System for property valuation in the flood-affected area; the system can analyse contributing factors in assessing the value of the property depending on the risk prediction of the flood event.

The implications of the results produced by this method are significant in terms of environmental disaster management. This method presents opportunities for other applications such as healthcare management, financial projection, image processing, and many others. The important thing is that this architecture reveals the maximum potential and usefulness of this architecture for modelling data in an integrated manner.

## 1.6 Thesis organisation

This thesis comprises the following contents:

- i. **Chapter 1: Introduction.** This chapter contains the research background, motivation, objectives to achieve, scope, and significance of the study.
- ii. **Chapter 2: Literature review.** This chapter reviews neural network models, explains the predictability of the environmental events, reasoning theory, data modelling approaches, suitable classification algorithms, and other related works.
- iii. **Chapter 3: Research methodology.** This chapter discusses the research phases, research framework, dataset collection, and data treatment, as well as the proposed approach for experimentation.
- iv. **Chapter 4: Results and analysis.** Presents each case studies and their corresponding experimental result, analyses, and discusses the result; including tangible and intangible factors that may be affecting the result.
- v. **Chapter 5: Conclusion and future works.** This chapter summarises and concludes the proposed work and provides recommendations for future continuation of work.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH



## CHAPTER 2

### LITERATURE REVIEW

#### 2.1 Introduction

This chapter elaborates on the evolution of neural networks and their generations. It also introduces environmental events occurrences patterns and nature of environmental-related data, and data patterns existing in nature. Along with this chapter, reasoning approaches and data modelling approaches are presented. Finally, suitable classification algorithms for the eSNN architecture are presented and justified.


#### 2.2 History of neural networks

The neural network is a collection of computational units (each referred to as a neuron or a perceptron) that are interlinked and may reside within a large system [16]. The artificial neural network has been inspired by the biological neural network mechanism [16]; designed to mimic its physiological behaviour hence allowing the network to replicate the decision-making capability of a biological brain.

In a series of five studies by Hodgkin and Huxley between 1951 and 1952 [17]–[21], the authors have explained the working mechanism of Hodgkin-Huxley model which is designed after an observation of the spikes and movement of action potentials (in the form of ions) in an axon of a giant squid. This is the first work that has used a mathematical model to explain the biological mechanism and has inspired many researchers to expand



## REFERENCES

- 
- [1] N. Kasabov, "Soft Computing Methods for Global, Local and Personalized Modeling and Applications in Bioinformatics," in *Soft Computing Based Modeling in Intelligent Systems*, vol. 196, Berlin, Heidelberg: Springer Berlin Heidelberg, 2009, pp. 1–18.
- [2] N. Kasabov, "Global, local and personalised modeling and pattern discovery in bioinformatics: An integrated approach," *Pattern Recognit. Lett.*, vol. 28, no. 6, pp. 673–685, Apr. 2007, doi: <https://doi.org/10.1016/j.patrec.2006.08.007>.
- [3] N. Kasabov *et al.*, "Evolving spiking neural networks for personalised modelling, classification and prediction of spatio-temporal patterns with a case study on stroke," *Neurocomputing*, vol. 134, pp. 269–279, Jun. 2014, doi: [10.1016/j.neucom.2013.09.049](https://doi.org/10.1016/j.neucom.2013.09.049).
- [4] N. K. Kasabov, "NeuCube: A spiking neural network architecture for mapping, learning and understanding of spatio-temporal brain data," *Neural Networks*, vol. 52, pp. 62–76, Apr. 2014, doi: [10.1016/j.neunet.2014.01.006](https://doi.org/10.1016/j.neunet.2014.01.006).
- [5] N. Kasabov, "NeuCube EvoSpike Architecture for Spatio-temporal Modelling and Pattern Recognition of Brain Signals," in *Artificial Neural Networks in Pattern Recognition*, 2012, pp. 225–243.
- [6] E. Tu *et al.*, "NeuCube(ST) for spatio-temporal data predictive modelling with a case study on ecological data," in *2014 International Joint Conference on Neural Networks (IJCNN)*, Jul. 2014, pp. 638–645, doi: [10.1109/IJCNN.2014.6889717](https://doi.org/10.1109/IJCNN.2014.6889717).
- [7] E. Capecci, N. Kasabov, and G. Y. Wang, "Analysis of connectivity in NeuCube spiking neural network models trained on EEG data for the understanding of functional changes in the brain: A case study on opiate dependence treatment," *Neural Networks*, vol. 68, pp. 62–77, Aug. 2015, doi: [10.1016/j.neunet.2015.07.011](https://doi.org/10.1016/j.neunet.2015.07.011).

- 10.1016/j.neunet.2015.03.009.
- [8] N. Kasabov, "Data analysis and Predictive Systems and Related Methodologies - Personalised Trait Modelling System.," *New Zeal. Pat. No. 572036, PCT/NZ2009/000222, NZ2009/000222-W16-79*, vol. 1, no. 19, 2008.
  - [9] R. N. Hartono, R. Pears, N. Kasabov, and S. P. Worner, "Extracting temporal knowledge from time series: A case study in ecological data," in *2014 International Joint Conference on Neural Networks (IJCNN)*, Jul. 2014, pp. 4237–4243, doi: 10.1109/IJCNN.2014.6889918.
  - [10] M. Othman *et al.*, "Improved predictive personalized modelling with the use of Spiking Neural Network system and a case study on stroke occurrences data," in *2014 International Joint Conference on Neural Networks (IJCNN)*, Jul. 2014, pp. 3197–3204, doi: 10.1109/IJCNN.2014.6889709.
  - [11] M. Othman, "Stroke risk prediction using Spiking Neural Network method," *Knowledge Engineering and Discovery Research Institute - AUT*, 2015. <https://kedri.aut.ac.nz/neucube/stroke>.
  - [12] S. Schliebs, H. N. A. Hamed, and N. Kasabov, "Reservoir-based evolving spiking neural network for spatio-temporal pattern recognition," in *International Conference on Neural Information Processing*, 2011, pp. 160–168.
  - [13] H. N. A. Hamed, N. Kasabov, S. M. Shamsuddin, H. Widiputra, and K. Dhoble, "An extended evolving spiking neural network model for spatio-temporal pattern classification," in *The 2011 International Joint Conference on Neural Networks*, 2011, pp. 2653–2656.
  - [14] M. Othman, S. A. Mohamed, M. H. A. Abdullah, M. M. Yusof, and R. Mohamed, "A Framework to Cluster Temporal Data Using Personalised Modelling Approach," in *Advances in Intelligent Systems and Computing*, vol. 700, 2018, pp. 181–190.
  - [15] M. H. A. Abdullah, M. Othman, S. Kasim, and S. A. Mohamed, "Evolving Spiking Neural Networks Methods for Classification Problem : A Case Study in Flood Events Risk Assessment Evolving spiking neural networks methods for classification problem : a case study in flood events risk assessment," *Indones. J. Electr. Eng. Comput. Sci.*, vol. 16, no. 1, pp. 222–229, 2019, doi:

10.11591/ijeecs.v16.i1.pp222-229.

- [16] B. Cheng and D. M. Titterington, "Neural networks: A review from a statistical perspective," *Stat. Sci.*, pp. 2–30, 1994.
- [17] A. L. Hodgkin, A. F. Huxley, and B. Katz, "Measurement of current-voltage relations in the membrane of the giant axon of Loligo," *J. Physiol.*, vol. 116, no. 4, pp. 424–448, 1951.
- [18] A. L. Hodgkin and A. F. Huxley, "Currents carried by sodium and potassium ions through the membrane of the giant axon of Loligo," *J. Physiol.*, vol. 116, no. 4, pp. 449–472, 1952.
- [19] A. L. Hodgkin and A. F. Huxley, "The components of membrane conductance in the giant axon of Loligo," *J. Physiol.*, vol. 116, no. 4, pp. 473–496, Apr. 1952, doi: 10.1113/jphysiol.1952.sp004718.
- [20] A. L. Hodgkin and A. F. Huxley, "The dual effect of membrane potential on sodium conductance in the giant axon of Loligo," *J. Physiol.*, vol. 116, no. 4, pp. 497–506, 1952.
- [21] A. L. Hodgkin and A. F. Huxley, "A quantitative description of membrane current and its application to conduction and excitation in nerve," *J. Physiol.*, vol. 117, no. 4, pp. 500–544, 1952.
- [22] F. Rosenblatt, "The perceptron: A probabilistic model for information storage and organization in the brain.," *Psychol. Rev.*, vol. 65, no. 6, pp. 386–408, Nov. 1958, doi: 10.1037/h0042519.
- [23] J. Gehlhaar, "Neuromorphic processing: A New Frontier in Scaling Computer Architecture," in *Proceedings of the 19th international conference on Architectural support for programming languages and operating systems - ASPLOS '14*, 2014, pp. 317–318, doi: 10.1145/2541940.2564710.
- [24] J. L. Lancaster *et al.*, "Automated Talairach atlas labels for functional brain mapping.," *Hum. Brain Mapp.*, vol. 10, no. 3, pp. 120–31, Jul. 2000, doi: 10.1002/1097-0193(200007)10:3<120::aid-hbm30>3.0.co;2-8.
- [25] J. L. Lancaster *et al.*, "Automated Labeling of the Human Brain: A Preliminary Report on the Development and Evaluation of a Forward-Transform Method," vol. 242, pp. 1–5, 2009, [Online]. Available: papers2://publication/uuid/99D4D45C-



CE70-4A9A-A6DC-97A349FF6587.

- [26] J. L. Lancaster *et al.*, “Automated labeling of the human brain: A preliminary report on the development and evaluation of a forward-transform method,” *Hum. Brain Mapp.*, vol. 5, no. 4, pp. 238–242, 1997, doi: 10.1002/(sici)1097-0193(1997)5:4<238::aid-hbm6>3.3.co;2-3.
- [27] Research Imaging Institute, “Talairach Applet.” <https://www.talairach.org/applet.html>.
- [28] T. Kitamura *et al.*, “Engrams and circuits crucial for systems consolidation of a memory,” *Science* (80-. ), vol. 356, no. 6333, pp. 73–78, Apr. 2017, doi: 10.1126/science.aam6808.
- [29] J. Baladron and F. H. Hamker, “A spiking neural network based on the basal ganglia functional anatomy,” *Neural Networks*, vol. 67, pp. 1–13, 2015.
- [30] W. Maass, “The third generation of neural network models,” 1997.
- [31] W. Maass, “Networks of spiking neurons: the third generation of neural network models,” *Neural Networks*, vol. 10, no. 9, pp. 1659–1671, 1997.
- [32] “originally published in: Bulletin of Mathematical Biophysics, Vol. 5, 1943, p. 115–133,” vol. 5, pp. 115–133, 2008.
- [33] I. Goodfellow, Y. Bengio, and A. Courville, *Deep learning*. MIT press, 2016.
- [34] J. von Kügelgen, “On Artificial Spiking Neural Networks: Principles, Limitations and Potential.”
- [35] W. Maass, “Liquid state machines: Motivation, theory, and applications,” *Comput. Context Comput. Log. Real World*, pp. 275–296, 2011, doi: 10.1142/9781848162778\_0008.
- [36] N. Kasabov *et al.*, “Evolving spatio-temporal data machines based on the NeuCube neuromorphic framework: Design methodology and selected applications,” *Neural Networks*, vol. 78, no. December, pp. 1–14, 2015, doi: 10.1016/j.neunet.2015.09.011.
- [37] J. Vreeken, “Spiking neural networks, an introduction.” Utrecht University: Information and Computing Sciences, 2003.
- [38] F. Y. Ahmed, B. Yusob, and H. N. A. Hamed, “Computing with spiking neuron networks: a review,” *Int. J. Adv. Soft Comput. Appl. Sydney*, vol. 6, pp. 1–21, 2014.



PTTA UTM  
PERPUSTAKAAN TUN AMINAH

- [39] A. A. Ghani, C. K. Chang, C. S. Leow, and N. A. Zakaria, "Sungai Pahang digital flood mapping: 2007 flood," *Int. J. River Basin Manag.*, vol. 10, no. 2, pp. 139–148, Jun. 2012, doi: 10.1080/15715124.2012.680022.
- [40] S. K. Sinnakaudan, A. Ab Ghani, M. S. S. Ahmad, and N. A. Zakaria, "Flood risk mapping for Pari River incorporating sediment transport," *Environ. Model. Softw.*, vol. 18, no. 2, pp. 119–130, Mar. 2003, doi: 10.1016/S1364-8152(02)00068-3.
- [41] P. Y. Julien, a. A. Ghani, N. a. Zakaria, R. Abdullah, and C. K. Chang, "Case Study: Flood Mitigation of the Muda River, Malaysia," *J. Hydraul. Eng.*, vol. 136, no. 4, pp. 251–261, Apr. 2010, doi: 10.1061/(ASCE)HY.1943-7900.0000163.
- [42] P. D. United Nations, Department of Economic and Social Affairs, "World Population Prospects: Key Findings & Advance Tables," 2017. [Online]. Available: <https://esa.un.org/unpd/wup/>.
- [43] Department of Irrigation and Drainage Malaysia, "Designated critical levels at a flood warning station."
- [44] Department of Irrigation and Drainage Malaysia, "River cross-section and designated critical water level at Kuala Krai flood warning station."
- [45] N. Kasabov, "NeuCube EvoSpike Architecture for Spatio-temporal Modelling and Pattern Recognition of Brain Signals," in *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, vol. 7477 LNAI, 2012, pp. 225–243.
- [46] N. Kasabov, K. Dhoble, N. Nuntalid, and G. Indiveri, "Dynamic evolving spiking neural networks for on-line spatio-and spectro-temporal pattern recognition," *Neural Networks*, vol. 41, pp. 188–201, 2013.
- [47] M. Di Luca and D. Rhodes, "Optimal perceived timing: Integrating sensory information with dynamically updated expectations," *Sci. Rep.*, vol. 6, no. 28563, 2016, doi: 10.1038/srep28563.
- [48] M. H. A. Abdullah, "Comparative Analysis of Spatio/Spectro-Temporal Data Modelling Techniques," in *Data Engineering And Information Security*, 1st ed., Penerbit UTHM, 2017.
- [49] E. Tu, N. Kasabov, and J. Yang, "Mapping Temporal Variables Into the NeuCube for Improved Pattern Recognition, Predictive Modeling, and Understanding of

- Stream Data,” *IEEE Trans. Neural Networks Learn. Syst.*, vol. 28, no. 6, pp. 1305–1317, Jun. 2017, doi: 10.1109/TNNLS.2016.2536742.
- [50] S. S. Saharuddin, N. Murli, and M. A. Hasibuan, “Classification of Spatio-Temporal fMRI Data in the Spiking Neural Network,” *Int. J. Adv. Sci. Eng. Inf. Technol.*, vol. 8, no. 6, pp. 2670–2676, 2018.
- [51] S. Kasim, M. F. M. Fudzee, M. A. Salamat, A. A. Ramli, H. Mahdin, and M. H. A. Abdullah, “An improved computational framework using one stage filtration by incorporating knowledge in gene expression clustering,” in *Proceedings of the International Conference on Artificial Intelligence and Robotics and the International Conference on Automation, Control and Robotics Engineering - ICAIR-CACRE '16*, 2016, pp. 1–5, doi: 10.1145/2952744.2952752.
- [52] S. Kasim, S. Deris, and R. M. Othman, “Multi-stage filtering for improving confidence level and determining dominant clusters in clustering algorithms of gene expression data,” *Comput. Biol. Med.*, vol. 43, no. 9, pp. 1120–1133, 2013.
- [53] Shaoning Pang and N. Kasabov, “Inductive vs transductive inference, global vs local models: SVM, TSVM, and SVMT for gene expression classification problems,” in *2004 IEEE International Joint Conference on Neural Networks (IEEE Cat. No.04CH37541)*, 2004, vol. 2, pp. 1197–1202, doi: 10.1109/IJCNN.2004.1380112.
- [54] V. Vladimir Naumovich and V. Vapnik, *Statistical learning theory*. New York: Wiley New York, 1998.
- [55] V. Vapnik, “The Support Vector Method of Function Estimation,” in *Nonlinear Modeling*, J. A. K. Suykens and J. Vandewalle, Eds. Boston, MA: Springer US, 1998, pp. 55–85.
- [56] G. Horvath, “CMAC: RECONSIDERING AN OLD NEURAL NETWORK Gábor Horváth,” 1992.
- [57] G. C. Cawley and N. L. C. Talbot, “On over-fitting in model selection and subsequent selection bias in performance evaluation,” *J. Mach. Learn. Res.*, vol. 11, pp. 2079–2107, 2010.
- [58] J. M. Keller, M. R. Gray, and J. A. Givens, “A fuzzy K-nearest neighbor algorithm,” *IEEE Trans. Syst. Man. Cybern.*, vol. SMC-15, no. 4, pp. 580–585, Jul.



- 1985, doi: 10.1109/TSMC.1985.6313426.
- [59] J. Derrac, F. Chiclana, S. Garcia, and F. Herrera, “An Interval Valued K-Nearest Neighbors Classifier,” 2015, doi: 10.2991/ifs-eusflat-15.2015.55.
- [60] K. Toduka and Y. Endo, “Fuzzy K-nearest Neighbor and its Application to Recognize of the Driving Environment,” in *2006 IEEE International Conference on Fuzzy Systems*, Jul. 2006, pp. 751–756, doi: 10.1109/FUZZY.2006.1681794.
- [61] N. Biswas, S. Chakraborty, S. S. Mullick, and S. Das, “A parameter independent fuzzy weighted k -Nearest neighbor classifier,” *Pattern Recognit. Lett.*, vol. 101, pp. 80–87, Jan. 2018, doi: 10.1016/j.patrec.2017.11.003.
- [62] M. Othman, “Spatial-temporal data modelling and processing for personalised decision support,” Auckland University of Technology, 2015.
- [63] M. G. Doborjeh and N. Kasabov, “Personalised modelling on integrated clinical and EEG spatio-temporal brain data in the NeuCube spiking neural network system,” in *2016 International Joint Conference on Neural Networks (IJCNN)*, 2016, pp. 1373–1378.
- [64] A. Almomani, M. Alauthman, F. Albalas, O. Dorgham, and A. Obeidat, “An online intrusion detection system to cloud computing based on NeuCube algorithms,” in *Cognitive Analytics: Concepts, Methodologies, Tools, and Applications*, IGI Global, 2020, pp. 1042–1059.
- [65] M. S. Brown, M. J. Pelosi, and H. Dirska, “Dynamic-Radius Species-Conserving Genetic Algorithm for the Financial Forecasting of Dow Jones Index Stocks,” in *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, vol. 7988 LNAI, 2013, pp. 27–41.
- [66] UCI Machine Learning Repository, “Dow Jones Index Data Set.” .
- [67] World Gold Council, “Goldhub.” .
- [68] S. Song, K. D. Miller, and L. F. Abbott, “Competitive Hebbian learning through spike-timing-dependent synaptic plasticity,” *Nat. Neurosci.*, vol. 3, no. 9, pp. 919–926, Sep. 2000, doi: 10.1038/78829.
- [69] S. Thorpe and J. Gautrais, “Rank order coding,” in *Computational neuroscience*, Springer, 1998, pp. 113–118.

- [70] A. Hamed and H. Nuzly, “Novel integrated methods of evolving spiking neural network and particle swarm optimisation,” Auckland University of Technology, 2012.
- [71] S. G. Wysoski, L. Benuskova, and N. Kasabov, “On-line learning with structural adaptation in a network of spiking neurons for visual pattern recognition,” *Lect. Notes Comput. Sci. (including Subser. Lect. Notes Artif. Intell. Lect. Notes Bioinformatics)*, vol. 4131 LNCS, pp. 61–70, 2006, doi: 10.1007/11840817\_7.
- [72] S. G. Wysoski, L. Benuskova, and N. Kasabov, “Text-independent speaker authentication with spiking neural networks,” *Lect. Notes Comput. Sci. (including Subser. Lect. Notes Artif. Intell. Lect. Notes Bioinformatics)*, vol. 4669 LNCS, no. PART 2, pp. 758–767, 2007, doi: 10.1007/978-3-540-74695-9\_78.
- [73] S. Loisel, J. Rouat, D. Pressnitzer, and S. Thorpe, “Exploration of rank order coding with spiking neural networks for speech recognition,” in *Proceedings. 2005 IEEE International Joint Conference on Neural Networks, 2005.*, 2005, vol. 4, pp. 2076–2080.
- [74] S. G. Wysoski, L. Benuskova, and N. Kasabov, “Fast and adaptive network of spiking neurons for multi-view visual pattern recognition,” *Neurocomputing*, vol. 71, no. 13–15, pp. 2563–2575, 2008.
- [75] N. K. Kasabov, *Evolving connectionist systems: the knowledge engineering approach*. Springer Science & Business Media, 2007.
- [76] H. N. Abdull Hamed, N. Kasabov, and S. M. Shamsuddin, *Quantum-inspired particle swarm optimization for feature selection and parameter optimization in evolving spiking neural networks for classification tasks*. InTech, 2011.
- [77] StackExchange, “How to choose the number of hidden layers and nodes in a feedforward neural network?” <https://stats.stackexchange.com/questions/181/how-to-choose-the-number-of-hidden-layers-and-nodes-in-a-feedforward-neural-netw> (accessed Nov. 12, 2020).
- [78] I. Goodfellow, Y. Bengio, and A. Courville, “Deep Learning (Adaptive Computation and Machine Learning Series).” e MIT Press, Cambridge, England, 2016.